

MOV Metal Oxide Varistors

Leaded varistors, TMOV High Surge, 14 series

Series/Type: VCRR14****K****

Ordering code: VCRR14****K

Date: January 2020

Version: 1

MOV metal oxide varistors

14****k****

Leaded varistors, TMOV High Surge, 14 series

VCRR14****K****

Construction

- Round varistor element, leaded
- Coating: epoxy resin, flame-retardant to UL 94 V-0
- Terminals: tinned wire

Features

- High performance with smaller disk diameter
- Wide operating voltage range 50 ... 680V_{RMS}
- High surge current ratings up to 6000 A
- No derating up to 85°C ambient temperature
- Series connection of varistors and fuses to disconnect when about to fail, protecting the circuit
- Action temperature 136C, matched with 5A.136C temperature fuse

Approvals

- UL Certificate:E531647
- TUV Certificate:B1199670002
- CQC Certificate :CQC23001399121

Delivery mode

- Bulk (standard), taped versions on reel or in Ammo pack upon request
- For further details refer to chapter "Taping, packaging and lead configuration" for leaded varistors.

General technical data

Climatic category	to IEC 60068-1	40/85/56	
Operating temperature	to IEC 61051	-40 ... +130	°C
Storage temperature		-40 ... +125	°C
Electric strength	to IEC 61051	≥ 2.5	kV _{RMS}
Insulation resistance	to IEC 61051	≥ 100	MΩ

MOV metal oxide varistors
14**k******
Leaded varistors, TMOV High Surge, 14 series
VCRR14**K******
Electrical specifications and ordering codes

Maximum ratings ($T_A = 85\text{ }^{\circ}\text{C}$)

Ordering code	Type	V_{RMS}	V_{DC}	i_{max} (8/20 μs) 1 time [A]*	$I_n^{1)}$ (8/20 μs) 15 times [A]*	W_{max} (10/1000 μs) [J]	P_{max} [W]
VCRR14*820KJ101	14*820KJ	50	65	6000	3000	30	0.1
VCRR14*101KJ101	14*101KJ	60	85	6000	3000	35	0.1
VCRR14*121KJ101	14*121KJ	75	100	6000	3000	42	0.1
VCRR14*151KJ101	14*151KJ	95	125	6000	3000	53	0.1
VCRR14*181KJ101	14*181KJ	115	150	6000	3000	74	0.6
VCRR14*201KJ101	14*201KJ	130	170	6000	3000	78.6	0.6
VCRR14*221KJ101	14*221KJ	140	180	6000	3000	80.5	0.6
VCRR14*241KJ101	14*241KJ	150	200	6000	3000	86	0.6
VCRR14*271KJ101	14*271KJ	175	225	6000	3000	94	0.6
VCRR14*301KJ101	14*301KJ	190	250	6000	3000	105	0.6
VCRR14*331KJ101	14*331KJ	210	270	6000	3000	115	0.6
VCRR14*361KJ101	14*361KJ	230	300	6000	3000	130	0.6
VCRR14*391KJ101	14*391KJ	250	320	6000	3000	140	0.6
VCRR14*431KJ101	14*431KJ	275	350	6000	3000	155	0.6
VCRR14*471KJ101	14*471KJ	300	385	6000	3000	175	0.6
VCRR14*511KJ101	14*511KJ	320	420	6000	3000	180	0.6
VCRR14*561KJ101	14*561KJ	350	460	6000	3000	186	0.6
VCRR14*621KJ101	14*621KJ	385	505	6000	3000	188	0.6
VCRR14*681KJ101	14*681KJ	420	560	6000	3000	190	0.6
VCRR14*751KJ101	14*751KJ	460	615	6000	3000	190	0.6
VCRR14*821KJ101	14*821KJ	510	670	6000	3000	210	0.6
VCRR14*911KJ101	14*911KJ	550	745	6000	3000	211	0.6
VCRR14*951KJ101	14*951KJ	575	765	6000	3000	235	0.6
VCRR14*102KJ101	14*102KJ	625	825	6000	3000	310	0.6
VCRR14*112KJ101	14*112KJ	680	895	6000	3000	330	0.6

¹⁾ **Note:** Nominal discharge current is the specification defined in UL1449 4th edition and tested with 8/20 μs current waveform

MOV metal oxide varistors

14****k****

Leaded varistors, TMOV High Surge, 14 series


VCRR14****K****

Characteristics (T_A=25 °C):

Ordering code	Type	V _V (1 mA) [V]	ΔV _V (1 mA) [%]	Max clamping voltage		C _{typ} (1 kHz) [pF]
				V _c [V]	I _c [A]	
VCRR14*820KJ101	14*820KJ	82	±10	135	50	2400
VCRR14*101KJ101	14*101KJ	100	±10	165	50	2000
VCRR14*121KJ101	14*121KJ	120	±10	200	50	1700
VCRR14*151KJ101	14*151KJ	150	±10	250	50	1300
VCRR14*181KJ101	14*181KJ	180	±10	300	50	1100
VCRR14*201KJ101	14*201KJ	200	±10	340	50	900
VCRR14*221KJ101	14*221KJ	220	±10	360	50	830
VCRR14*241KJ101	14*241KJ	240	±10	395	50	740
VCRR14*271KJ101	14*271KJ	270	±10	455	50	670
VCRR14*301KJ101	14*301KJ	300	±10	500	50	610
VCRR14*331KJ101	14*331KJ	330	±10	550	50	560
VCRR14*361KJ101	14*361KJ	360	±10	595	50	510
VCRR14*391KJ101	14*391KJ	390	±10	650	50	460
VCRR14*431KJ101	14*431KJ	430	±10	710	50	430
VCRR14*471KJ101	14*471KJ	470	±10	775	50	390
VCRR14*511KJ101	14*511KJ	510	±10	840	50	360
VCRR14*561KJ101	14*561KJ	560	±10	910	50	320
VCRR14*621KJ101	14*621KJ	620	±10	1025	50	290
VCRR14*681KJ101	14*681KJ	680	±10	1120	50	270
VCRR14*751KJ101	14*751KJ	750	±10	1240	50	260
VCRR14*821KJ101	14*821KJ	820	±10	1355	50	230
VCRR14*911KJ101	14*911KJ	910	±10	1500	50	220
VCRR14*951KJ101	14*951KJ	950	±10	1570	50	200
VCRR14*102KJ101	14*102KJ	1000	±10	1650	50	180
VCRR14*112KJ101	14*112KJ	1100	±10	1815	50	130

2) *Please refer to the suffix code

Schematic Diagram:




MOV metal oxide varistors

14****k****

Leaded varistors, TMOV High Surge, 14 series

VCRR14****K****

Dimensional drawings



Weight

Nominal diameter mm	V _{RMS} V	Weight g
14	50...680	1.2...4.7

Different voltage levels result in differences in weight.

Dimensions

Ordering code ²⁾	[e1/e2] ±1 mm	W _{max} mm	h _{max} mm	th _{max} mm	a _{typ} mm	l _{min} mm	Ød±0.05 mm
VCRR14*820KJ101	7.5/5	17	19	7	4.3	25.0	0.8
VCRR14*101KJ101	7.5/5	17	19	7	4.3	25.0	0.8
VCRR14*121KJ101	7.5/5	17	19	7	4.3	25.0	0.8
VCRR14*151KJ101	7.5/5	17	19	7	4.3	25.0	0.8
VCRR14*181KJ101	7.5/5	17	19	7	4.5	25.0	0.8
VCRR14*201KJ101	7.5/5	17	19	8	4.5	25.0	0.8
VCRR14*221KJ101	7.5/5	17	19	8	4.5	25.0	0.8
VCRR14*241KJ101	7.5/5	17	19	8	4.5	25.0	0.8
VCRR14*271KJ101	7.5/5	17	19	8.5	4.5	25.0	0.8
VCRR14*301KJ101	7.5/5	17	19	8.7	4.5	25.0	0.8
VCRR14*331KJ101	7.5/5	17	19	8.8	4.5	25.0	0.8
VCRR14*361KJ101	7.5/5	17	19	9	4.6	25.0	0.8
VCRR14*391KJ101	7.5/5	17	19	9.1	4.8	25.0	0.8
VCRR14*431KJ101	7.5/5	17	19	9.4	5.0	25.0	0.8
VCRR14*471KJ101	7.5/5	17	19	9.6	5.1	25.0	0.8
VCRR14*511KJ101	7.5/5	17	19	9.8	5.3	25.0	0.8
VCRR14*561KJ101	7.5/5	17	19	10.1	5.3	25.0	0.8
VCRR14*621KJ101	7.5/5	17	19	10.2	5.8	25.0	0.8
VCRR14*681KJ101	7.5/5	17	19	10.3	5.4	25.0	0.8
VCRR14*751KJ101	7.5/5	17	19	10.7	6.1	25.0	0.8
VCRR14*821KJ101	7.5/5	17	19	11.1	6.4	25.0	0.8
VCRR14*911KJ101	7.5/5	17	19	11.5	6.7	25.0	0.8
VCRR14*951KJ101	7.5/5	17	19	11.9	6.9	25.0	0.8
VCRR14*102KJ101	7.5/5	17	19	11.9	7.1	25.0	0.8
VCRR14*112KJ101	7.5/5	17	19	12.0	7.4	25.0	0.8

2) *Please refer to the suffix code.

MOV metal oxide varistors
14**k******
Leaded varistors, TMOV High Surge, 14 series
VCRR14**K******
Reliability data

Test	Test methods/conditions	Requirement
Varistor voltage	The voltage between two terminals with the specified measuring current applied is called V_V (1 mA _{DC} @ 0.2 ... 2 s).	To meet the specified value
Clamping voltage	The maximum voltage between two terminals with the specified standard impulse current (8/20 μ s) applied.	To meet the specified value
Endurance at upper category temperature	1000 h at UCT After having continuously applied the maximum allowable AC voltage at UCT ± 2 °C for 1000 h, the specimen shall be stored at room temperature and normal humidity for 1 to 2 h. Thereafter, the change of V_V shall be measured.	$ \Delta V/V (1 \text{ mA}) \leq 10\%$
Surge current derating, 8/20 μ s	10 surge currents (8/20 μ s), unipolar, interval 30 s, amplitude corresponding to derating curve for 10 impulses at 20 μ s	$ \Delta V/V (1 \text{ mA}) \leq 10\%$ (measured in direction of surge current) No visible damage
Surge current derating, 2 ms	10 surge currents (2 ms), unipolar, interval 120 s, amplitude corresponding to derating curve for 10 impulses at 2 ms	$ \Delta V/V (1 \text{ mA}) \leq 10\%$ (measured in direction of surge current) No visible damage
Electric strength	IEC 61051-1, test 4.9.2 Metal balls method, 2500 VRMS, 60 s The varistor is placed in a container holding 1.6 ± 0.2 mm diameter metal balls such that only the terminations of the varistor are protruding. The specified voltage shall be applied between both terminals of the specimen connected together and the electrode inserted between the metal balls.	No breakdown

MOV metal oxide varistors
14**k******
Leaded varistors, TMOV High Surge, 14 series
VCRR14**K******

Test	Test methods/conditions	Requirement
Climatic sequence	The specimen shall be subjected to: a) dry heat at UCT, 16 h, IEC 60068-2-2, test Ba b) damp heat, 1st cycle: 55 °C, 93% r. H., 24 h, IEC 60068-2-30, test Db c) cold, LCT, 2 h, IEC 60068-2-1, test Aa d) damp heat, additional 5 cycles: 55 °C/25 °C, 93% r. H., 24 h/cycle, IEC 60068-2-30, test Db. Then the specimen shall be stored at room temperature and normal humidity for 1 to 2 h. Thereafter, the change of V_V shall be measured. Thereafter, insulation resistance R_{ins} shall be measured at $V = 500$ V.	$ \Delta V/V (1 \text{ mA}) \leq 10\%$ $R_{ins} \geq 100 \text{ M}\Omega$
Rapid change of temperature	IEC 60068-2-14, test Na, LCT/UCT, dwell time 30 min, 5 cycles	$ \Delta V/V (1 \text{ mA}) \leq 5\%$ No visible damage
Damp heat, steady state	IEC 60068-2-78, test Ca The specimen shall be subjected to 40 ± 2 °C, 90 to 95% r. H. for 56 days without load / with 10% of the maximum continuous DC operating voltage VDC. Then stored at room temperature and normal humidity for 1 to 2 h. Thereafter, the change of V_V shall be measured. Thereafter, insulation resistance R_{ins} shall be measured at $V = 500$ V (insulated varistors only).	$ \Delta V/V (1 \text{ mA}) \leq 10\%$ $R_{ins} \geq 100 \text{ M}\Omega$

MOV metal oxide varistors

14****k****

Leaded varistors, TMOV High Surge, 14 series

VCRR14****K****

Test	Test methods/conditions	Requirement
Solderability	IEC 60068-2-20, test Ta, method 1 with modified conditions for lead-free solder alloys: 245 °C, 3 s: After dipping the terminals to a depth of approximately 3 mm from the body in a soldering bath of 245 °C for 3 s, the terminals shall be visually examined.	The inspection shall be carried out under adequate light with normal eyesight or with the assistance of a magnifier capable of giving a magnification of 4 to 10 times. The dipped surface shall be covered with a smooth and bright solder coating with no more than small amounts of scattered imperfections such as pinholes or un-wetted or de-wetted areas. These imperfections shall not be concentrated in one area.
Resistance to soldering heat	IEC 60068-2-20, test Tb, method 1A, 260 °C, 10 s: Each lead shall be dipped into a solder bath having a temperature of 260 ±5 °C to a point 2.0 to 2.5 mm from the body of the specimen, be held there for 10 ±1 s and then be stored at room temperature and normal humidity for 1 to 2 h. The change of VV shall be measured and the specimen shall be visually examined.	$ \Delta V/V (1 \text{ mA}) \leq 5\%$ No visible damage
Tensile strength	IEC 60068-2-21, test Ua1 After gradually applying the force specified below and keeping the unit fixed for 10 s, the terminal shall be visually examined for any damage. Force for wire diameter: 0.6 mm = 10 N 0.8 mm = 10 N 1.0 mm = 20 N	$ \Delta V/V (1 \text{ mA}) \leq 5\%$ No break of solder joint, no wire break

MOV metal oxide varistors
14**k******
Leaded varistors, TMOV High Surge, 14 series
VCRR14**K******

Test	Test methods/conditions	Requirement
Vibration	IEC 60068-2-6, test Fc, method B4 Frequency range: 10 ... 55 Hz Amplitude: 0.75 mm or 98 m/s ² Duration: 6 h (3 · 2 h) Pulse: sine wave After repeatedly applying a single harmonic vibration according to the table above. The change of V _V shall be measured and the specimen shall be visually examined.	ΔV/V (1 mA) ≤5% No visible damage
Bump	IEC 60068-2-29, test Eb Pulse duration: 6 ms Max. acceleration: 400 m/s ² Number of bumps: 4000 Pulse: half sine	ΔV/V (1 mA) ≤5% No visible damage
Fire hazard	IEC 60695-11-5 (needle flame test) Severity: vertical 10 s	5 s max.

Note:

UCT = Upper category temperature


LCT = Lower category temperature

R_{ins} = Insulation resistance

v/i characteristics

$v = f(i)$ - for explanation of the characteristics refer to "General technical information".


A = Leakage current, B = Protection level } for worst-case varistor tolerances



Derating curves

Maximum surge current $i_{\max} = f(t_r, \text{pulse train})$

For explanation of the derating curves refer to "General technical information",



Taping, packaging and lead configuration


1 JORDUN Electronics ordering code system for leaded varistors

VCRR	14	N/M/E	471	K	0	1	0	1	1
logo									
Disc Diameter									
Design structure: N: 2 Pin M: Fuse is pin 2 E: Fuse is pin 3									
Varistor Voltage: 471:470V 561:560V 470:47V 102:1000V									
Tolerance of Varistor Voltage: K=±10% J=±5% S=Special tolerance									
Design: J=High Joule N=High Energy T=Automotive Remark: eg:printing 14N561KJ or 14E561KJ or 14M561KJ									
Lead Configuration: 1=Straight Leads 2=Inner Pin 3=Forward and Backward Pin 4=Outer K Pin Please refer to "Standard leads and non-standard crimp styles"									
Packaging: 0=Bulk 1=Taping Style for further information please refer to chapter "Taping, packaging and lead configuration"									
Bulk Pin Length: 1=3.5±0.5mm 2=3.0±0.5mm 3=4.0±0.5mm 4=25±0.5mm 5=5.0±0.5mm									
Internal Coding: ABCDEF									

2 Taping and packaging of leaded varistors

Tape packaging for lead spacing $\boxed{e} = 5$ fully conforms to IEC 60286-2, while for lead spacings $\boxed{e} = 7.5$ and 10 the taping mode is based on this standard.


2.1 Taping in accordance with IEC 60286-2 for lead spacing 5.0 mm



$F \triangleq \boxed{e} = 5.0 \text{ mm}$

VAR0410-X-E

2.2 Taping based on IEC 60286-2 for lead spacing 7.5 and 10 mm



$F \triangleq \boxed{e} = 7.5 \text{ mm}$

$F \triangleq \boxed{e} = 10 \text{ mm}$

VAR0395-J-E

MOV metal oxide varistors
14* *K******
Leaded varistors, TMOV High Surge, 14series
VCRR14**K ******
2.3 Tape dimensions (in mm)


Symbol	$e = 5.0$	Tolerance	$e = 7.5$	Tolerance	$e = 10.0$	Tolerance	Remarks
w th d	0.6	max. max. ± 0.05	0.8	max. max. ± 0.05	1.0	max. max. ± 0.05	see tables in each series under "Dimensions "
P ₀	12.7	± 0.3	12.7 ¹⁾	± 0.3	12.7	± 0.3	± 1 mm/20 sprocket holes
P ₁	3.85	± 0.7	8.95	± 0.8	7.7	± 0.8	
F	5.0	± 10	7.5	± 0.8	10.0	± 0.8	measured at top of compo- nent body
Δh	0	± 2.0	depends on s		depends on s		
Δp	0	± 1.3	0	± 2.0	0	± 2.0	
W	18.0	± 0.5	18.0	± 0.5	18.0	± 0.5	Peel-off force ≥ 5 N
W ₀	5.5	min.	11.0	min.	11.0	min.	
W ₁	9.0	± 0.5	9.0	$+0.75/-0.5$	9.0	$+0.75/-0.5$	
W ₂	3.0	max.	3.0	max.	3.0	max.	
H	18.0	$+2.0/-0$	18.0	$+2.0/-0$	18.0	$+2.0/-0$	²⁾ ³⁾
H ₀	16.0	± 0.5	16.0	± 0.5	16.0	± 0.5	
	(18.0)		(18.0)				
H ₁	32.2	max.	45.0	max.	45.0	max.	
D ₀	4.0	± 0.2	4.0	± 0.2	4.0	± 0.2	without lead
t	0.9	max.	0.9	max.	0.9	max.	
L	11.0	max.	11.0	max.	11.0	max.	
L ₁	0.5	max.					

1) Taping with P₀ = 15.0 mm upon request

2) Applies only to uncrimped types

3) Applies only to crimped types (H₀ = 18 upon request)

2.4 Ammo pack dimensions



2.5 Quantities Per Packaging

Part No	Voltage	Bulk		Ammo Packing(Taping)	
		Bag	Carton	Box	Carton
7D	181-821	1000	12000	1000	10000
10D	180-182	500	6000	1000	10000
14D	180-182	500	6000	800	8000
20D	180-182	250	3000	----	----
25D	180-182	200	2400	----	----

3 Lead configuration

Straight leads are standard for disk varistors. Other lead configurations as crimp style or customerspecific lead wire length according to 3.1, 3.2, 3.3 and 3.4 are optional. Crimped leads (non-standard) are differently crimped for technical reasons; the individual crimp styles are denot-ed by consecutive numbers (S, S2 through S5) as shown in the dimensional drawings below.

The crimp styles of the individual types can be seen from the type designation in the ordering tables.

3.1 Standard leads and non-standard crimp styles

The basic dimensions in figure 1 to 5 are valid for types with either round or square (EnergetiQ series) component head

**Standard,
straight leads**




Figure 1

**Non-standard,
crimp style S2**




Figure 2

**Non-standard,
crimp style S3**





Figure 3

**Non-standard,
crimp style S5**



Figure

3.2 Trimmed leads (non-standard)


Varistors with cut leads available upon request.

Lead length tolerances:

Straight leads ± 0.8 mm

Crimped leads ± 0.5 mm

Minimum lead length 3.0 mm



1) Seating plane to IEC 60717

*) For round component head

**) For EnergetiQ series, square component head

VAR0642-U-E

Cautions and warnings

General

1. JORDUN Electronics metal oxide varistors (MOV) are designed for specific applications and should not be used for purposes not identified in our specifications, application notes and data books unless otherwise agreed with JORDUN Electronics during the design-in-phase.
2. Ensure suitability of MOV through reliability testing during the design-in phase. The MOV should be evaluated taking into consideration worst-case conditions.
3. For applications of MOV in line-to ground circuits based on various international and local standards there are restrictions existing or additional safety measures required.

Storage

1. Store MOV only in original packaging. Do not open the package prior to processing.
2. Recommended storage conditions in original packaging:

Storage temperature:	-25 °C ... +45 °C
Relative humidity:	<75% annual average, <95% on maximum 30 days a year.
Dew precipitation:	Is to be avoided.
3. Avoid contamination of an MOV's during storage, handling and processing.
4. Avoid storage of MOVs in harmful environments that can affect the function during long-term operation (examples given under operation precautions).
5. The MOV type series should be soldered after shipment from JORDUN ELECTRONIC within the time specified.

MOV-J,N,T	24 months
-----------	-----------

Handling

1. MOVs must not be dropped.
2. Components must not be touched with bare hands. Gloves are recommended.
3. Avoid contamination of the surface of MOV electrodes during handling, be careful of the sharp edge of MOV electrodes.

Soldering (where applicable)

1. Use rosin-type flux or non-activated flux.
2. Insufficient preheating may cause ceramic cracks.

3. Rapid cooling by dipping in solvent is not recommended.
4. Complete removal of flux is recommended.
5. Temperatures of all preheat stages and the solder bath must be strictly controlled especially for T series

Mounting

1. Potting, sealing or adhesive compounds can produce chemical reactions in the MOV ceramic that will degrade the component's electrical characteristics.
2. Overloading MOVs may result in ruptured packages and expulsion of hot materials. For this reason the MOVs should be physically shielded from adjacent components.

Operation

1. Use MOVs only within the specified temperature operating range
2. Use MOVs only within the specified voltage and current ranges.
3. Environmental conditions must not harm the MOVs. Use MOVs only in normal atmospheric conditions. Avoid use in the presence of deoxidizing gases (chlorine gas, hydrogen sulfide gas, ammonia gas, sulfuric acid gas, etc), corrosive agents, humid or salty conditions, Avoid contact with any liquids and solvents.

Symbols and terms

Symbol	Term
C	Capacitance
C _{typ}	Typical capacitance
i	Current
i _c	Current at which V _{c, max} is measured
I _{leak}	Leakage current
i _{max}	Maximum surge current (also termed peak current)
I _{max}	Maximum discharge current
I _n	Nominal discharge current to UL 1449
LCT	Lower category temperature
L _{typ}	Typical inductance
P _{max}	Maximum average power dissipation
R _{ins}	Insulation resistance
R _{min}	Minimum resistance
T _A	Ambient temperature
t _r	Duration of equivalent rectangular wave
UCT	Upper category temperature
v	Voltage
V _{clamp}	Clamping voltage
V _{c, max}	Maximum clamping voltage at specified current i _c DC operating voltage
V _{DC}	Maximum jump start voltage
V _{jump}	Maximum voltage
V _{max}	Operating voltage
V _{op}	AC operating voltage, root-mean-square value
V _{RMS}	Root-mean-square value of max. DC operating voltage incl. ripple current
V _{RMS, op, max}	Super imposed surge voltage
V _{surge}	Varistor voltage
V _V	Tolerance of varistor voltage
ΔV _V	
W _{LD}	Maximum load dump
W _{max}	Maximum energy absorption
	Lead spacing

All dimensions are given in mm.

The commas used in numerical values denote decimal points.

Release:Version January,2020